

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations


Printing date: April 20, 2018

Revision: April 20, 2018

1 Identification

- **Product identifier**
- **Trade name:** DT-6060
- **Other means of identification:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Coating material
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Dyna-Tek LLC.
5300 E. 59th Street
Kansas City, MO 64130
USA
(816) 444-6266
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Acute Tox. 4 H302 Harmful if swallowed.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

GHS02 GHS05 GHS07
- **Signal word:** Danger
- **Hazard statements:**
H225 Highly flammable liquid and vapor.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
- **Precautionary statements:**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 1)

P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist, vapors, or spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection.
P301+P312	If swallowed: Call a poison center/doctor if you feel unwell.
P330	Rinse mouth.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

108-21-4	isopropyl acetate  Flam. Liq. 2, H225  Eye Irrit. 2A, H319; STOT SE 3, H336	50-75%
	Trade Secret  Flam. Liq. 2, H225  Skin Corr. 1B, H314; Eye Dam. 1, H318  Acute Tox. 4, H302	15-55%
	Naphtha (petroleum), light alkylate  Asp. Tox. 1, H304	<10%
	Trade Secret  Skin Corr. 1B, H314  Acute Tox. 4, H302; Skin Sens. 1, H317	<2%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements, refer to section 16.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 2)

4 First-aid measures

- **Description of first aid measures**

- **After inhalation:**

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

Seek medical help for symptoms or if unconscious.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Do not pull solidified product away from the skin.

Wash with soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

- **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

Remove contact lenses if worn.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

- **Most important symptoms and effects, both acute and delayed:**

Breathing difficulty

Dizziness

Coughing

Irritant to skin and mucous membranes.

Eye damage.

Allergic reactions

- **Danger:**

Harmful if swallowed.

Danger of impaired breathing.

- **Indication of any immediate medical attention and special treatment needed:**

If necessary oxygen respiration treatment.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

Alcohol resistant foam

Carbon dioxide

Gaseous extinguishing agents

Fire-extinguishing powder

Water fog / haze

- **For safety reasons unsuitable extinguishing agents:**

Water stream.

Water spray

- **Special hazards arising from the substance or mixture**

Highly flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

- **Advice for firefighters**

- **Protective equipment:**

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 3)

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Eliminate all ignition sources if safe to do so.

Cool endangered containers with water fog.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions Avoid release to the environment.**Methods and material for containment and cleaning up**

Allow to solidify. Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling**Precautions for safe handling:**

Use only in well ventilated areas.

Keep out of reach of children.

Open and handle receptacle with care.

Avoid contact with the eyes and skin.

Avoid breathing mist, vapors, or spray.

Information about protection against explosions and fires:

Highly flammable liquid and vapor.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

Conditions for safe storage, including any incompatibilities**Requirements to be met by storerooms and receptacles:**

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Protect from humidity and water.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 4)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

108-21-4 isopropyl acetate

PEL (USA)	Long-term value: 950 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 626 mg/m ³ , 150 ppm Long-term value: 417 mg/m ³ , 100 ppm
EL (Canada)	Short-term value: 200 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 200 ppm Long-term value: 100 ppm
LMPE (Mexico)	Short-term value: 200 ppm Long-term value: 100 ppm

- **Exposure controls**

- **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.
 Keep away from foodstuffs, beverages and feed.
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.

- **Engineering controls:** Provide adequate ventilation.

- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

- **Protection of hands:**



Protective gloves

- **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No relevant information available.

- **Risk management measures** No relevant information available.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

Form: Liquid
Color: According to product specification

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 5)

· pH-value:	Not determined.
· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	92 °C (197.6 °F)
· Flash point:	<15 °C (<59 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Not determined.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	0.89
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with Water:	Slowly reacts with water.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Highly flammable liquid and vapor.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Reacts with oxidizing agents.
Reacts with peroxides.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 5)

- **Hazardous decomposition products**

Under fire conditions only:
Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:** Harmful if swallowed.

- **LD/LC50 values that are relevant for classification:**

919-30-2 3-aminopropyltriethoxysilane

Oral	LD50	1780 mg/kg (rat)
Dermal	LD50	4000 mg/kg (rabbit)

475645-84-2 cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine

Oral	LD50	>300-2000 mg/kg (rat)
------	------	-----------------------

- **Primary irritant effect:**

- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Strong irritant with the danger of severe eye injury.

- **Sensitization:**

Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.
Sensitization possible through skin contact.

- **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

- **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

- **Carcinogenicity:** Based on available data, the classification criteria are not met.

- **Reproductive toxicity:** Based on available data, the classification criteria are not met.

- **STOT-single exposure:** May cause drowsiness or dizziness.

- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity**

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 7)

Harmful to aquatic life with long lasting effects.

475645-84-2 cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine


LC50 | 57.1 mg/l (zebra fish)

- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**
 Avoid release to the environment.
 Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1139
- **UN proper shipping name**
- **DOT, IATA** Coating solution
- **ADR, IMDG** COATING SOLUTION
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 8)

· ADR


· **Class** 3 (F1) Flammable liquids
 · **Label** 3

· IMDG, IATA


· **Class** 3 Flammable liquids
 · **Label** 3

· Packing group

· **DOT, ADR, IMDG, IATA** II

· Environmental hazards

· **Marine pollutant:** No

· Special precautions for user

Warning: Flammable liquids

· Danger code (Kemler):

33

· EMS Number:

 F-E, S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:
· DOT


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· ADR


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IMDG


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IATA


Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 9)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· Section 302 (extremely hazardous substances):
--

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):
--

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):
--

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)
--

All ingredients are listed.

- **Proposition 65 (California)**

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):
--

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients listed on DSL or NDSL.
--

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** April 20, 2018 / -

- **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: April 20, 2018

Revision: April 20, 2018

Trade name: DT-6060

(Cont'd. of page 10)

PBT: Persistent, Bio-accumulable, Toxic
vPvB: very Persistent and very Bioaccumulative
OSHA: Occupational Safety & Health Administration
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor_internet/registry/substreg/home/overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com