

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

1 Identification

- Product identifier
- Trade name: DT-420 Mold Sealer
- Other means of identification: No other identifiers

Recommended use and restriction on use

- Recommended use: Coating material
- * Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier: Dyna-Tek LLC. 5300 E. 59th Street Kansas City, MO 64130 USA (816) 444-6266

• Emergency telephone number: ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Danger

· Hazard statements:

H225 Highly flammable liquid andvapor.

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

(Cont'd. on page 2)



YNA-TEK

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

Trade name: DT-420

			(Cont'd. of page 1)
•	Precautionary sta		
	P210	Keep awayfrom heat/sparks/open flames/hot surfaces No smoking.	
	P233	Keep container tightly closed.	
	P240	Ground/bond container and receiving equipment.	
	P241	Use explosion-proof electrical/ventilating/lighting/equipment.	
	P242	Use only non-sparking tools.	
	P243	Take precautionary measures against staticdischarge.	
	P261	Avoid breathing dust/fume/gas/mist/vapors/spray	
	P264	Wash thoroughly after handling.	
	P270	Do not eat, drink or smoke when using thisproduct.	
	P271	Use only outdoors or in a well-ventilated area.	
	P272	Contaminated work clothing must not be allowed out of the workplace.	
	P280	Wear protective gloves/protective clothing/eye protection.	
	P301+P310	If swallowed: Immediately call a poison center/doctor.	
	P330	Rinse mouth.	
	P331	Do NOT induce vomiting.	
	P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse	e skin with
		water/shower.	
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breat	hing.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove co	ontact lenses, if
		present and easy to do. Continue rinsing.	
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
	P363	Wash contaminated clothing before reuse.	
	P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.	
	P403+P235	Store in ventilated area, dry area, ideally between 55°-65°.	
	P405	Store locked up.	
	P501	Dispose of contents/container in accordance with local/regional/national	/international
		regulations.	
•	Other hazards ⊤	here are no other hazards not otherwise classified that have been identifi	ed.

3 Composition/information on ingredients

Chemical characterization: Mixtures

· Components		
64741-66-8	Naphtha (petroleum), light alkylate	10-15%
	🚸 Asp. Tox. 1, H304	
108-21-4	isopropyl acetate	15-30%
	Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	
	Trade Secret	15-30%
	Flam. Liq. 2, H225	
	Skin Corr. 1B, H314; Eye Dam. 1, H318	
	Acute Tox. 4, H302	
64742-47-8	Distillates (petroleum), hydrotreated light	<10%
	Flam. Liq. 3, H226	
	Asp. Tox. 1, H304	
	Skin Irrit. 2, H315; STOT SE 3, H336	
	(Cont'd	. on page 3)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

Trade name: DT-420

Trade Secret

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures Description of first aid measures · After inhalation: Supply fresh air. Provide oxygen treatment if affected person has difficulty breathing. Seek medical help for symptoms or if unconscious. In case of unconsciousness place patient stably in side position for transportation. After skin contact: Do not pull solidified product away from the skin. Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor. Remove contact lenses if worn. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; immediately call for medical help. A person vomiting while lying on their back should be turned onto their side. Most important symptoms and effects, both acute and delayed: Breathing difficulty Dizziness Coughing Irritant to skin and mucous membranes. Eve damage. Allergic reactions · Danger: Harmful if swallowed. Danger of impaired breathing. May be fatal if swallowed and enters airways. Indication of any immediate medical attention and special treatment needed: If swallowed or in case of vomiting, danger of entering the lungs. If necessary oxygen respiration treatment. Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: Alcohol resistant foam Carbon dioxide

(Cont'd. on page 4)

(Cont'd. of page 2)

<10%



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

Trade name: DT-420

(Cont'd. of page 3)

Gaseous extinguishing agents Fire-extinguishing powder Water fog / haze For safety reasons unsuitable extinguishing agents: Water stream. Water spray Special hazards arising from the substance or mixture Highly flammable liquid and vapor. Formation of toxic gases is possible during heating or in case of fire. Advice for firefighters Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit. Additional information: Eliminate all ignition sources if safe to do so. Cool endangered containers with water fog.

6 Accidental release measures

[•] Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions Avoid release to the environment.

• Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling

Precautions for safe handling:

Use only in well ventilated areas. Keep out of reach of children. Open and handle receptacle with care. If the container exhibits any signs of expansion, open the cap slowly allowing expansion gas to escape. Avoid contact with the eyes and skin. Avoid breathing mist, vapors, or spray.

Information about protection against explosions and fires:

Highly flammable liquid and vapor.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

[•] Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

(Cont'd. on page 5)



DYNA-TEK

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

rade name: DT-420		
Do not store near Protect from humi Information abou Store away from for Store away from c	t storage in one common storage facility: podstuffs.	
8 Exposure co	ntrols/personal protection	
The following co recommended e At this time, the o	ith limit values that require monitoring at the workplace: nstituents are the only constituents of the product which have a PEL, TLV or other xposure limit. other constituents have no known exposure limits.	
108-21-4 isopro		
PEL (USA) TLV (USA)	Long-term value: 950 mg/m ³ , 250 ppm Short-term value: 626 mg/m ³ , 150 ppm Long-term value: 417 mg/m ³ , 100 ppm	
EL (Canada)	Short-term value: 200 ppm Long-term value: 100 ppm	
EV (Canada)	Short-term value: 200 ppm Long-term value: 100 ppm	
LMPE (Mexico)	Short-term value: 200 ppm Long-term value: 100 ppm	
64742-47-8 Dist	illates (petroleum), hydrotreated light	
EL (Canada)	Long-term value: 200 mg/m³ Skin	
Always observe sa Keep away from fo Wash hands befor Avoid contact with • Engineering co • Breathing equip • Protection of ha	tive and hygienic measures: afe precautionary measures for handling chemicals should be followed. bodstuffs, beverages and feed. e breaks and at the end of work. Do not inhale gases / fumes / aerosols. the eyes and skin. ntrols: Provide adequate ventilation. oment: Use suitable respiratory protective device in case of insufficient ventilation. ands: we gloves	
	(Cont'd. on page 6	



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

Follow relevant national safety guidel • Body protection: Protective work clo • Limitation and supervision of e No relevant information available. • Risk management measures No	xposure into the environment
Physical and chemical prope	erties
· Information on basic physical a	and chemical properties
· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
• Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	104 °C (219.2 °F)
· Flash point:	<15 °C (<59 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
Explosion limits	
Explosion limits Lower:	Not determined.
Upper:	Not determined.
• Oxidizing properties:	Not determined.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	0.8
Vapor density:	Not determined.
Evaporation rate:	Not determined.
•	
 Solubility in / Miscibility with Water: 	Slowly reacts with water.
· Partition coefficient (n-octanol/wat	ter): Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No relevant information available.

(Cont'd. on page 7)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

Trade name: DT-420

(Cont'd. of page 6)

10 Stability and reactivity Reactivity: No relevant information available. Chemical stability: Stable under normal temperatures and pressures. Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications. Possibility of hazardous reactions Highly flammable liquid and vapor. Used empty containers may contain product gases which form explosive mixtures with air. Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized. Reacts with oxidizing agents. Reacts with peroxides. Toxic fumes may be released if heated above the decomposition point. Conditions to avoid Excessive heat. Incompatible materials Oxidizers Hazardous decomposition products

Under fire conditions only: Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)

11 Toxicological information

Information on toxicological effects

Acute toxicity: Harmful if swallowed.

· LD/LC50 values that are relevant for classification:

475645-84-2 cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine

Oral LD50 >300-2000 mg/kg (rat)

919-30-2 3-aminopropyltriethoxysilane

Oral LD50 1780 mg/kg (rat)

Dermal LD50 4000 mg/kg (rabbit)

Primary irritant effect:

• On the skin: Irritant to skin and mucous membranes.

• On the eye: Strong irritant with the danger of severe eye injury.

Sensitization: Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

• NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Inhalation.

(Cont'd. on page 8)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

Trade name: DT-420

(Cont'd. of page 7)

- Eye contact.
- Skin contact.
- · Germ cell mutagenicity: Based on available data, the classification criteria are notmet.
- \cdot Carcinogenicity: Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- · STOT-single exposure: May cause drowsiness or dizziness.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: May be fatal if swallowed and enters airways.

12 Ecological information

- Toxicity
- Aquatic toxicity

Harmful to aquatic life with long lasting effects.

475645-84-2 cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanamine

LC50 57.1 mg/l (zebra fish)

- · Persistence and degradability No relevant information available.
- Bioaccumulative potential: No relevant information available.
- **Mobility in soil:** No relevant information available.
- Additional ecological information
- General notes:
- Avoid release to the environment.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

[•] Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

14 Transport information

(Cont'd. on page 9)



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations


Revision: February 4, 2021

	(Cont'd. of pa
UN-Number DOT, ADR, IMDG, IATA	UN1139
UN proper shipping name DOT, IATA ADR, IMDG	Coating solution COATING SOLUTION
Transport hazard class(es) DOT	
Class Label	3 Flammable liquids 3
ADR	~
Class Label	3 (F1) Flammable liquids 3
IMDG, IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	II
Environmental hazards Marine pollutant:	No
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids 33 F-E <u>,S-E</u>
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information: DOT Limited Quantity for packages less t	han 30 kg gross and inner packagings less than 5 L each



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021



Safety, health and environmental regulations/legislation specific for the substance or mixture United States (USA) SARA · Section 302 (extremely hazardous substances): None of the ingredients are listed. · Section 355 (extremely hazardous substances): None of the ingredients are listed. · Section 313 (Specific toxic chemical listings): None of the ingredients are listed. · TSCA (Toxic Substances Control Act) All ingredients are listed. **Proposition 65 (California)** · Chemicals known to cause cancer: None of the ingredients are listed. · Chemicals known to cause developmental toxicity for females: None of the ingredients are listed. · Chemicals known to cause developmental toxicity for males: None of the ingredients are listed. · Chemicals known to cause developmental toxicity: None of the ingredients are listed. · EPA (Environmental Protection Agency): None of the ingredients are listed. (Cont'd. on page 11)



acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: February 4, 2021

Trade name: DT-420

(Cont'd. of page 9)

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL):

All ingredients listed on DSL or NDSL.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision April 20, 2018 / -

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistant, Bio-accumulable, Toxic vPvB: very Persistent and very Bioaccumulative OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com