



SAFETY AND STORAGE WARNINGS – READ UPON RECEIPT!

**PLEASE BE SURE TO READ THE INSTRUCTIONS BELOW PRIOR TO ADDING
DYNA-TEK COATINGS INTO YOUR INVENTORY STORAGE.**

**IMPROPER STORAGE CONDITIONS OF DYNA-TEK COATING PRODUCTS WILL LIKELY LEAD TO A
SHORTER SHELF LIFE OF DYNA-TEK PRODUCTS. PLEASE NOTE THE INSTRUCTIONS BELOW.**

TEMPERATURE, SUNLIGHT and HUMIDITY RESTRICTIONS

Dyna-Tek products should be stored where there is no sunlight, in climate-controlled areas designed for hazardous (flammable) storage with temperatures of no more than 70° F. to 50° F. with relatively low humidity. If left in temperatures over 70° F for extended periods of time, extended periods of storage in temperatures over 70° F can cause the performance properties of these products to diminish.

INSPECTIONS PRIOR TO ENTERING THE INVENTORY INTO STORAGE

Always inspect each container for signs of damage such as deep scratches, loosely sealed caps, and expansion upon receipt, and prior to placing into storage. Thereafter, we recommend visually inspecting the containers for signs of expansion every 30 days while in inventory/storage.

PRODUCT SHELF LIFE

Dyna-Tek products have a shelf life of 12 months for properly stored and unopened containers.

SAFETY PRECAUTIONS

Please read the Safety Data Sheets for both products prior to opening any containers.

Always use caution when opening containers. Be sure to look for signs of any pressure build-up (expansion) of the container prior to opening. If expansion of the sides has occurred, slowly open the screw-on cap, and release the gas pressure in a well-ventilated area before opening it the rest of the way.

If you have any issues with the shipment you have received, or have any suggestions on how we can improve our service, packaging or any other areas; please do not hesitate to email us at CustomerService@Dyna-Tek.com or call us at 855.500.6266.

05202024